

- 1 -
TITLE

IMPROVED APPARATUS FOR THE COLD STERILIZATION OF A FLUID
BY ULTRAVIOLET RAYS

DESCRIPTION

5 Field of the Invention

The present invention refers to the field of fluid sterilization and more precisely has as its object an improved apparatus for continuous cold sterilization of a fluid by ultraviolet rays.

10 Description of the state of the art

In cold sterilization of fluids lamps are used arranged in the immediate vicinity of the fluid to be treated and capable of emitting ultraviolet wavelength radiation which, as known, has strong germicide
15 properties.

In some types of cold sterilizing apparatuses, the lamps are sunk into the container with the fluid to be sterilized, whereas, in other types, the fluid passes through tubes, made of material permeable to ultraviolet
20 radiation, which are exposed to the rays of the lamps arranged nearby. Amongst the known configurations of this second type of apparatus there are two that are more common having, in the first case, linear lamps surrounded by a bundle of tubes parallel to them and, in a second
25 case, many parallel lamps arranged between two curtains of parallel tubes.

The results that can be obtained with cold sterilization through ultraviolet rays is all the better the longer the exposure of the fluid to the action of the
30 ultraviolet radiation and the more the material of the tubes in which the fluid circulates is permeable to this radiation. Nevertheless, in the two configurations of the

second type of apparatus described above, to obtain a treatment path of sufficient length, it is necessary to arrange a large number of lamps in series giving rise to a correspondingly bulk apparatus or, alternatively, it is
5 necessary to excessively slow down the speed of the fluid in the transparent tubes creating problems of insufficient capacity of the apparatus in the case in which high fluid flow rates must be treated.

Again in this type of cold sterilizer, with fluid
10 that flows in transparent tubes and that is exposed to ultraviolet radiation, there are also another two drawbacks. The first is the incomplete exploitation of the radiation that, filtering through the tubes and the fluid, dissipates on the inner walls of the apparatus. The second
15 is represented by the risk of incomplete or even inexistent sterilization in the case in which the lamp is switched off or has run out.

An apparatus for the continuous cold sterilization of a fluid that overcomes the aforementioned drawbacks has
20 been produced and commercialised by the same Applicant. In this apparatus a duct transparent to ultraviolet radiation and extending helically around the ultraviolet radiation source has been provided. A tubular screen is arranged outside of and coaxially to the helical duct. This
25 apparatus, whilst operating satisfactorily, has the drawback of excessively heating the water mainly when there is a low water demand and when the lamp has been switched on for a long time. In these circumstances, the water, staying still for a long time in the helical duct,
30 can immediately be used only at a substantially higher temperature than room temperature and can also reach temperature levels unsuitable for the apparatus and for

- 3 -

the user.

Objects and summary of the invention

The objects of the present invention is to provide an apparatus for the continuous cold sterilization of a fluid that allows the aforementioned problems to be solved and more specifically that does not have the drawback of the heating of the fluid without however penalizing the exploitation of the ultraviolet radiation emitted by the lamp and therefore the sterilizing capability of the apparatus.

This and other objects are accomplished with the continuous cold sterilization apparatus according to the present invention, the essential features of which consist in that the helical portion of the duct for the fluid is arranged in a chamber with walls having reflective surfaces and in that the distance between the walls and the helical portion is sufficient to allow the circulation of air between them. Moreover, the helical portion of the duct for the fluid has an elliptical-shaped passage section with the major axis perpendicular to the irradiation direction.

Brief description of the drawings

Further characteristics and advantages of the apparatus for the cold sterilization of a fluid by ultraviolet rays according to the present invention shall become clearer from the following description of an embodiment thereof, given as a non-limiting example, with reference to the attached drawing, in which:

- figure 1 is a sectional view of the apparatus made according to a vertical plane passing through the axis of the lamp;

- figure 2 is an enlarged view of the detail indicated with A in figure 1.

- figure 3 is a side view of the apparatus.

Detailed description of the invention

5 With reference to the aforementioned figures, an apparatus for continuously cold sterilizing a fluid comprises a box-shaped casing 1, at least one ultraviolet radiation source 2, of the linear tubular lamp type, and at least one duct 3 permeable to such radiation in which a
10 fluid to be sterilized 4 flows. The duct 3 has a portion 3a that extends helically around the source 2, so that all of the radiation emitted by it crosses the fluid 4 and exerts the germicide action. At its outlet the duct 3 is connected to a dispensing device 10.

15 According to the invention, the helical portion 3a of the duct 3 is arranged in a chamber 1a of the box-shaped casing 1 defined by the walls of the casing 1 and by an inner wall 6. The inner surface of said walls has good characteristics of reflection to ultraviolet
20 radiation, said walls preferably being made from stainless steel. In this way the residual ultraviolet radiation, passing through the helical portion 3a and the fluid that flows in it, is reflected onto the fluid to be treated. To avoid the heating of the water during some steps of the
25 sterilization process, the helical portion 3a of the duct 3 is suitably spaced from the wall 6 and from the outer wall of the casing 1, such a distance, indicated with d in figure 1, being at least equal to 5 mm and preferably equal to 15 mm.

30 Thanks to the teaching of suitably spacing the walls of the chamber 1a from the tubular portion 3a, the air

- 5 -

circulation and heat exchange is promoted. Also contributing to achieving such a result is the presence of slits 9, shown in figure 3, formed on the walls of the chamber 1a that allow the circulation of air between the chamber 1a and the outside.

In order to avoid a loss of treatment efficiency due to the distance between the reflective surfaces and the helical portion 3a, the latter has an elliptical-shaped passage section 5 for the fluid with its major axis parallel to the axis of the tubular light source 2 or, in general, perpendicular to the irradiation direction. The squashing of the section of the tube forming the tubular portion 3a significantly decreases the thickness of the fluid that the light radiation must cross thus realising a significant gain in efficiency somewhat greater than the loss of efficiency due to the distancing of the reflective surface.

The control of the operation of the apparatus and in particular of the irradiation conditions is carried out through an indicator light 7 fixed to the outside of the casing 1 and communicating optically with the lamp 2 by means of an optical fibre 8 positioned in contact with the lamp or in its immediate vicinity. By checking the operation through the indicator light 7 it is possible to find out whether the apparatus is working correctly and in particular to prevent drawbacks like the switching off or the running out of the lamp that can impair the quality of sterility of the outlet fluid 4.

Advantageously, the duct 3, or at least its helical portion 3a, is made from teflon or equivalent materials.

The apparatus according to the invention fully achieves the predetermined purposes. In particular, it allows a fluid in transit through the duct 3 to be sterilized increasing the efficiency with respect to the previously known solution and keeping the temperature at completely acceptable values, in any case never greater than those reached by the lamp 2, even in the most extreme operating conditions quoted previously.

Variations and/or modifications may be brought to the apparatus for continuously cold sterilizing a fluid according to the present invention, without departing from the scope of the invention as defined in the attached claims.

- 7 -

CLAIMS

1. Apparatus for the continuous cold sterilization of a fluid comprising at least one ultraviolet radiation source and at least one duct permeable to such radiation in which
5 said fluid flows, said duct having a portion that extends helically around said source, characterised in that said helical portion is arranged in a chamber the walls of which have reflective surfaces, the distance between said walls and said helical portion being sufficient to allow
10 the circulation of air between them, said helical portion of the duct for the fluid having an elliptical-shaped passage section with the major axis perpendicular to the irradiation direction.
2. Apparatus according to claim 1, wherein air circulation
15 slits are formed on the walls of said chamber.
3. Apparatus according to claims 1 or 2, wherein the distance between the walls of said chamber and said helical portion is at least 5 mm.
4. Apparatus according to any one of the previous claims,
20 wherein said ultraviolet radiation source is tubular-shaped and the major axis of the elliptical section of said helical portion is parallel to the longitudinal axis of said source.
5. Apparatus according to any one of the previous claims,
25 wherein outside of said chamber an indicator light is provided and is optically connected to said ultraviolet radiation source through an optical fibre placed in contact with the lamp or in its immediate vicinity.

THIS PAGE BLANK (USPTO)




FIG. 1




FIG. 2

FIG. 2

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

Application No
PCT/IT2004/000346

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61L2/10 C02F1/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61L C02F A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/096648 A1 (KAISER KLAUS ET AL) 25 July 2002 (2002-07-25) paragraphs '0012!', '0014!', '0017!', '0024! - '0027!', '0030! - '0033!', '0041! - '0043!', '0066!; claims 1-3,6,7	1,3-5
A	US 4 968 437 A (NOLL ET AL) 6 November 1990 (1990-11-06) column 3, lines 10-43 column 5, lines 4-66 column 7, line 68 - column 8, line 5; figures 1,2,15,16	1,3-5
A	US 5 874 741 A (MATSCHE ET AL) 23 February 1999 (1999-02-23) column 1, line 66 - column 2, line 31 column 4, lines 24-58; figure 2	1,3,4
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

15 February 2005

Date of mailing of the international search report

23/02/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.

Authorized officer

...

INTERNATIONAL SEARCH REPORT

Inte Application No
PCT/IT2004/000346

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		Relevant to claim No.
Category *	Citation of document, with indication, where appropriate, of the relevant passages	
A	<p>EP 0 378 716 A (TUCKER, ROBERT E) 25 July 1990 (1990-07-25) column 2, lines 10-26 column 4, line 7 - column 5, line 42; figures</p> <p>-----</p>	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int Application No
PCT/IT2004/000346

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2002096648	A1	25-07-2002	DE 10056096 A1	13-06-2002
			AU 1906602 A	21-05-2002
			CA 2428264 A1	16-05-2002
			CN 1486282 T	31-03-2004
			WO 0238502 A1	16-05-2002
			EP 1339643 A1	03-09-2003
			JP 2004512912 T	30-04-2004
US 4968437	A	06-11-1990	US 5004541 A	02-04-1991
			AT 116552 T	15-01-1995
			AU 601743 B2	20-09-1990
			AU 7396687 A	01-12-1987
			CA 1293847 C	07-01-1992
			CN 87103349 A ,B	25-11-1987
			DE 3750950 D1	16-02-1995
			DE 3750950 T2	24-05-1995
			EP 0267261 A1	18-05-1988
			IE 68061 B1	15-05-1996
			IL 82292 A	05-11-1990
			IN 168752 A1	01-06-1991
			JP 1500016 T	12-01-1989
			JP 2974676 B2	10-11-1999
			KR 9105289 B1	24-07-1991
			MX 167742 B	12-04-1993
			NO 880069 A ,B,	09-03-1988
			NZ 220069 A	28-05-1990
			OA 8594 A	30-11-1988
			PT 84827 A ,B	01-06-1987
			WO 8706841 A1	19-11-1987
			US 4769131 A	06-09-1988
US 5874741	A	23-02-1999	CA 2247652 A1	17-03-2000
			US 5612001 A	18-03-1997
EP 0378716	A	25-07-1990	CA 1320813 C	03-08-1993
			US 4798702 A	17-01-1989
			EP 0378716 A1	25-07-1990
			ES 2048772 T3	01-04-1994

THIS PAGE BLANK (USPTO)